



CAVIBLASTER™

Model - 2040

Specifications and Options

SKID	
Dimensions:	
Height	64" / 163 cm
Width	55" / 140 cm
Length	62" / 157 cm
Weight	2,400 # / 1,100 kg
Fuel/Oil Containment Pan	Yes
Lifting Eyes / Forklift Slots	Yes / Yes

PUMP SYSTEM	
Pressure Pump	CAT Pumps Model 3560
Pump Type – Manifold Material	Triplex plunger – Stainless steel
Flow Rate	20 gpm / 76 lpm
Nozzle Pressure	3,700 psi / 255 bar
Hose Diameter - Max. Length	3/4" - 600 LF / 200 m

FEED SYSTEM	
Feed Pump	Pacer Pumps I Series
Pump Material & Type	Stainless steel self-priming centrifugal
Maximum Lift	20' / 6 m

DRIVE SYSTEM	
Engine	Kubota V3600
Engine Type	4-cylinder liquid-cooled
Intake System	Naturally aspirated
Combustion System	Indirect fuel injection
Power Output - Maximum	67 HP / 50 kW
Power Output - Continuous	53 HP / 40 kW
Clutch Type	Power take-off (PTO)
Starting System	Air
Emergency Shut-offs - Automatic	Low oil pressure / High oil temperature / High coolant temperature
Emergency Shut-off - Manual	Engine air intake

