

- ACETAL (Plastic)
- Color or B&W Camera.



USES INCLUDE: HELMET MOUNT, MANIPULATOR ARM, HAND-HELD, DROP CAMERA, ETC.

MODEL#	UWC-300 (BLACK & WHITE)	UWC-325 (COLOR)
Image Device	1/3" CCD Sensor 411,000, Pixels.	1/3" DSP CCD Sensor 412,000 Pixels.
Sensitivity	.0003 lux	0.001 lux
Resolution	600 Horz. lines.	750 Horz. lines
PWR (12-24 VDC)	@ 110 ma.	@ 110 ma.
Lens	E-Iris, 3.6mm F1.2	E-Iris, 3.6mm F1.2
Horz. FOV	70 deg. In Water	70 deg. In water


MECHANICAL:

Length..... 5 in. (125mm)
(excluding connector).
Diameter..... 1.58 in. (40mm)
Weight..... Dry 6 oz. (.2kg)
Wet 3 oz. (.08kg)
Depth Rating..... 2000 ft. (600 m)
Housing..... Black Delrin

CONNECTOR:

Standard Connector..... XSK-5-BCL
(Mate is RMK-5-FS)

1. Video (White)
2. Ground/Common (Black)
3. +12-24 VDC (Green)



OPTIONS:

1. CCIR (PAL) Format
2. Customer specified connector
3. 3000+ meter, SAPPHIRE port